

DUAL JACK BASE

The Dual Jack Base is designed specifically to use with Dual Rack Rails and Dual Jack Flashing. It is one of the strongest methods for installing solar panels. Each Dual Jack Base comes with two 5/16" x 4" hex head stainless steel lag bolts and two EPDM-bonded sealing washers. It allows for up to 4 structural attachments when required. The Dual Jack Base is available in clear or black finishes.

ADVANTAGES

- Compatible with all Dual Jack (standoff) sizes.
- Compatible with Dual Jack Flashing to prevent wind-driven rain water exposure.
- Allows up to 4 structural attachments when required, for an even stronger installation.
- Easy install method saves time and labor cost.
- Cost effective.
- Clear and black anodized product available.
- 10 Year limited warranty.
- Conforms to UL STD 2703 and Class A Fire Rated.

Component List

Material	QTY
Dual Jack Base	01
5/16" x 4" SS Hex Lag Bolt	02
5/16" Sealing Washer	02

Ordering Specifics

	Qty / Box	Weight / Box	Box Size
Unit Package	1 pc / Box	0.6 lbs / Box	4.5" (L) x 4.5" (W) x 1.5" (H)
Small Box	10 pcs / Box	6.0 lbs / Box	25.0" (L) x 10.0" (W) x 1.8" (H)
Big Box	40 pcs / Box	24.0 lbs / Box	25.0" (L) x 10.0" (W) x 8.5" (H)



Installation Guide

For detailed installation please refer to the Dual Rack installation guide



Hand tighten ONLY, with a required torque of 15 lbs., when securing the Dual Rack Base to Dual Rack attachments.

Product Line

Item #	Product Name	
DR-CDJB-01	Dual Jack Base - Clear	 DR-CDJB-01_Dual Jack Base - Clear
DR-BDJB-01	Dual Jack Base - Black	 DR-BDJB-01_Dual Jack Base - Black

