



DUAL JACK FLASHING

Our Dual Jack Flashing comes in 12.0" x 12.0" and 9.0" x 12.5" sizes (Clear or Black color) and is designed to be used on composition/asphalt shingle roofs. Get a simple, watertight seal every time.

ADVANTAGES

- Clear and black product available.
- 10 Year limited warranty.
- Conforms to UL STD 2703 and Class A Fire Rated.

Component List

Material	QTY
Aluminum Flashing	01
EPDM	01

Ordering Specifics

Product	DR-CDJF-01 / DR-BDJF-01	DR-CDJF-01 / DR-BDJF-01
Net Weight	0.41 lbs	0.54 lbs
Standard Pack	Set of 10/ box	Set of 10 / box
Standard Pack Dimension	13.0" (L) x 9.5" (W) x 3.0" (H)	13.0" (L) x 13.0" (W) x 3.0" (H)
Standard Pack Weight	4.5 lbs / box	5.7 lbs / box
Big Pack	Set of 40 / box	Set of 40 / box
Big Pack Pack Dimension	13.0" (L) x 9.5" (W) x 12.0" (H)	13.0" (L) x 13.0" (W) x 12.0" (H)
Big Pack Weight	18.5 lbs / box	23.3 lbs / box

Installation Guide

For detailed installation please refer to the Dual Rack installation guide



1. After securing the Dual Jack roof attachment to the roof, cut a piece of the shingle if required.



2. Gently break seal between shingles and remove any nails.



3. Slide flashing up under shingles and recover the roof with the shingle.



4. Apply fresh compatible sealant around the Dual Jack roof attachment.* Recommended.



5. Press the EPDM down and hold to secure in place.

Product Line

Item #	Product Name
DR-CDJF-01	Dual-Jack Flashing - Clear (9.0" x 12.5")
DR-CDJF-02	Dual-Jack Flashing - Clear (12.0" x 12.0")
DR-BDJF-01	Dual-Jack Flashing - Black (9.0" x 12.5")
DR-BDJF-02	Dual-Jack Flashing - Black (12.0" x 12.0")

